



- NOTES:**
1. RESIDENTIAL POLES SHALL BE FLUTED OR SMOOTH ALUMINUM WITH BLACK FINISH.
 2. COMMERCIAL POLES SHALL BE ROUND TAPERED ALUMINUM WITH GALVANIZED, ALUMINUM, OR BLACK FINISH.
 3. LOADING CAPACITY OF POLE SHALL BE 100 POUND RATED FOR A STEADY WIND OF 90 MPH MINIMUM.
 4. CONCRETE BASES SHALL BE BACKFILLED WITH SUITABLE MATERIAL COMPACTED TO 95 PERCENT.
 5. CONCRETE BASES SHALL HAVE REINFORCING CAGE CONSISTING OF #4 REBAR @ 6" O.C. BOTH WAYS.
 6. CONCRETE BASES SHALL INCLUDE CONDUIT AND GROUNDING WIRE PER HEBER LIGHT & POWER REQUIREMENTS.

STREET LIGHTING

V:\ENGR\Stus\StusSpec\StusSpec 2019\Drawg Files\STREETS-12.dwg - 85x11 - 1/23/2019 04:57pm, rfrnk

HORROCKS

ENGINEERS
 728 WEST 100 SOUTH #2
 HEBER CITY, UTAH 84032
 (435) 654-2226

DATE:	FEBRUARY 2019
SCALE:	N.T.S.
	75 NORTH MAIN STREET HEBER CITY, UTAH 84032 (435) 654-0757

HEBER CITY
 HEART OF THE WASATCH BACK

HEBER CITY
STANDARD DRAWING

STREETS-12